DIAL INDICATORS



Face Type A

- Range 1.0"
- Graduations .001"
- Reading 0-100
- Diameter 2-1/4"
- · Continuous forward and reverse
- Rack and pinion construction
- Reading with revolution counter

Indicator No.	Included in Set Nos.	Description
4345	6410,6419,6615	Lug back, 3/8" dia. shank
4343	6470	Flat back, 1/2" dia. shank
4344	6413,6448,6450,6454	Lug back, 1/2" dia. shank
4341	6482,6487	Lug back, 1/2" dia. shank
	•	(set screw and 1" contact point included)
4374	6434	Lug back, 1/2" dia. shank with flat contact



4345

Face Type B

- Range 30mm
- Graduations .01mm
- Reading 0-2.0
- Diameter 2-1/4"
- Continuous forward and reverse
- Rack and pinion construction
- Reading with revolution counter

Indicator No.	Included in Set Nos.	Description
4393	6409,6411,6616	Lug back, 3/8" dia. shank
4392	6414,6449,6451	Flat back, 1/2" dia. shank
4390	6483	Lug back, 1/2" dia. shank
4398	-	Lug back, 1/2" dia. shank
		(set screw and 1" contact point included)



4393

Face Type C

- Range .200"
- Graduations .001"
- Continuous

- Reading 0-100
- Diameter 1-1/2"
- Jeweled bearing construction

Indicator No.	Included in Set Nos.	Description
4346	6400,6405	Back plunger, 1/4" dia. shank



4346

Face Type D

- Range 5.0mm
- Graduations .02mm
- Continuous

- Reading 0-2.0
- Diameter 1-1/2"
- Jeweled bearing construction

Indicator No.	Included in Set Nos.	Description
. 4394	6402,6407	Back plunger, 1/4" dia. shank
4396	6463	Back plunger, no shank



4394

DIAL INDICATORS



Face Type E

• Range .200"

Graduations .001"

Balanced

Reading 0-50-0

Diameter 1-1/2"

• Jeweled bearing construction

Indicator No.	Included in Set Nos.	Description
4347		Back plunger, 1/4" dia. shank
4348		Back plunger, no shank



4347

Face Type G

• Range 5.0mm

• Reading 0-100

• Graduations .01mm

• Diameter 1-5/8"

Continuous with revolution counter
Rack and pinion construction

Indicator No.	Included in Set Nos.	Description
4342	6491	Flat back, 3/8" dia. shank
4587		Flat back, 1/2" dia. shank



4342

Face Type H

• Range .200"

• Graduations .0005"

Balanced

DISCONTINUED

• Reading 0-20-0

• Diameter 1-5/8"

Rack and pinion construction

Indicator No.	Included in Set Nos.	Description
4389	6460	Flat back, no shank



4389

Face Type I

DISCONTINUED

• Range 5.0mm

Reading 0-100

• Graduations .01mm

• Diameter 1-5/8"

Continuous

· Rack and pinion construction

Indicator No.	Included in Set Nos.	Description
4395	6461	Flat back, no shank



4395

Face Type J

• Range .100"

• Graduations .0001"

· Continuous reverse reading with revolution counter

• Reading 0-10

• Diameter 2-1/4"

 Rack and pinion construction and fully jeweled

Indicator No.	Included in Set Nos.	Description
4580	6467	Flat back, 8mm dia. shank




4580

Central Tools, Inc. offers a wide range of contact points which allow you to use your Central dial indicator for a variety of applications. All contact points have AGD standard 4-48 thread.

Standard Contact Points


- Polished tip with radius end
- Hardened steel



~"A"	" PART NO."
.100	4201
.200	4304
.400	4305
.600	4306
.800	4307
1.000	4210
1.500	4211
2.000	4222
2.290	4989

Spherical Contact Points


- Polished tip with spherical end
- Hardened steel



**************************************	"B"	PART NO.
.110	5/16"	4202
.125	3/4"	4340

Contact Extensions

- 4-48 female thread allows you to extend any contact point for special applications.
- Several extensions may be joined together for extra long reach.



Α"	PART NO.
1.000	4214
6.000	4851
12.000	4852

Special Contact Points

